



Flex series

Unlimited Versatile Shape combination
Unmatched Visual effect performance

Wide Choice selections

Various Pixel pitch selections
Various module size selections

Highly customizable

Pixel pitch and size of the module are all customizable



Magnetic module design

Strong magnet to hold the module on the frame firmly

Easy to install

Led module can attach to the customized frame very easily to form different shapes

Easy maintenance

Front service maintenance, can easily replacing failure led module from front

Module No.	FL0.93	FL1.25	FL1.5	FL1.6	FL1.8	FL2	FL2.5	FL3	FL4
Size:	240*120mm	○240*120mm ●320*160mm	○240*120mm ●320*160mm	○240*120mm ●320*160mm	○240*120mm ●320*160mm	○240*120mm ●320*160mm	○240*120mm ●320*160mm	○240*120mm ●320*160mm	○240*120mm ●320*160mm
Pixel Pitch:	0.9375mm	1.25mm	○1.579mm ●1.538mm	○1.579mm ●1.538mm	○1.875mm ●1.86mm	2mm	2.5mm	○3mm ●3.076mm	4mm
Weight(g):	○170g ●270g	○170g ●270g	○170g ●270g	○170g ●270g	○170g ●270g	○170g ●270g	○170g ●270g	○170g ●270g	○170g ●270g
SMD Chip:	Mini 4 in 1 COB available	SMD1010 COB available	SMD1212 COB available	SMD1212	SMD1515/ SMD1212	SMD1515	SMD1515	SMD2121	SMD2121
Pixel density (dot/㎡)	1137777	640000	○401111 ●422500	○401111 ●422500	○284444 ●288906	250000	160000	○111111 ●105625	62500
Resolution:	256x128	○192*96 ●256*128	○152*76 ●208*104	○152*76 ●208*105	○126*64 ●172*86	○120*60 ●160*80	○96*48 ●128*64	○80*40 ●104*52	○60*30 ●80*40
Scan mode:	1/64	○1/48 ●1/64	○1/38 ●1/52	○1/38 ●1/53	○1/32 ●1/43	○1/30 ●1/40	○1/24 ●1/32	○1/20 ●1/26	○1/15 ●1/20
Refresh Rate	3840Hz	3840Hz	3840Hz	3840Hz	3840Hz	3840Hz	3840Hz	3840Hz	3840Hz
Brightness (cd/㎡)	500-600nit	600-700nit	700-900nit	700-900cd	700-900nit	700-900nit	700-900nit	700-900nit	700-900nit
Wattage (Max./Avg.)	600W/200W	600W/200W	600W/200W	600W/200W	600W/200W	600W/200W	600W/200W	600W/200W	600W/200W
Viewing Angle(H/V)	160°/140°								
CCT:	1000-10000K Changeable								
Contrast Ratio:	5000:1								
Maintenance:	Front								

