



Floor LED Display Built in interactive sensor






LOB Version Specs Sheet




Model No.	LO1.25	LO1.5	LO1.95	LO2.6	LO2.97	LO3.91	
Pixel Pitch (mm)	1.25mm	1.524mm	1.95mm	2.6mm	2.97mm	3.91mm	
Led Lamp	SMD1010	SMD1212	SMD1515	SMD1515	SMD1515	SMD192	
Pixel Density (dot/ m²)	640000	430336	262144	147456	112896	65536	
Cabinet Resolution	400*400	328*328	256*256	192*192	168*168	128*128	
Weight (Kg/ Cabinet)	12kg	12kg	12kg	12kg	12kg	12kg	
Refresh Rate (Hz)	3840	3840	3840	3840	3840	3840	
Brightness (cd/ m²)	800-1200nit						
Life span	≥ 100,000Hours						
Greyscale	14bit						
MAX Wattage (W/ m²)	800W						
Working Wattage (W/ m²)	300W						
IP Grade	IP67/IP54						
Input Voltage	AC100~240V 50/60Hz						
Module Size(mm)	250mm*250mm						
Cabinet Size (mm)	500mm*500mm*89mm						
Maintenance	Back						
Working Environment	Temperature -20~50°C						



Mask Version Specs Sheet



Model No.	MA2.5	MA2.6	MA2.97	MA3.91	MA4.81	MA5.2	
Pixel Pitch (mm)	2.5mm	2.6mm	2.97mm	3.91mm	4.81mm	5.2mm	
Led Lamp	SMD1415	SMD1415	SMD1415	SMD1921	SMD1921	SMD1921	
Pixel Density (dot/ m²)	160000	147456	112896	65536	43264	36864	
Cabinet Resolution	200*200	192*192	168*168	128*128	104*104	96*96	
Weight (Kg/ Cabinet)	12kg	12kg	12kg	12kg	12kg	12kg	
Refresh Rate (Hz)	3840	3840	3840	3840	3840	3840	
Brightness (cd/ m²)	800-1200nit						
Life span	≥ 100,000Hours						
Greyscale	14bit						
MAX Wattage (W/ m²)	800W						
Working Wattage (W/ m²)	300W						
IP Grade	IP67/IP54						
Input Voltage	AC100~240V 50/60Hz						
Module Size(mm)	250mm*250mm						
Cabinet Size (mm)	500mm*500mm*89mm						
Maintenance	Back						
Working Environment	Temperature -20~50℃						









Stair LED Display Specs Sheet



Model No.	ST2.97			
Pixel Pitch (mm)	2.97mm			
Led Lamp	SMD1515			
Pixel Density (dot/ m²)	112896			
Cabinet Resolution	168*168			
Weight (Kg/ Cabinet)	12kg			
Refresh Rate (Hz)	3840			
Brightness (cd/ m²)	800-1200nit			
Life span	≥ 100,000Hours			
Greyscale	14bit			
MAX Wattage (W/ m²)	800W			
Working Wattage (W/ m²)	300W			
IP Grade	IP67/IP54			
Input Voltage	AC100~240V 50/60Hz			
Module Size(mm)	250mm*250mm			
Cabinet Size (mm)	1000mm*300mm*66mm / 1000*150mm*66mm			
Maintenance	Back			
Working Environment	Temperature -20~50°C			