



**Tunnel LED Display**  
360° immersive visual effect



## Tunnel LED Display Specs

Module No.	FL0.93	FL1.25	FL1.5	FL1.6	FL1.8	FL2	FL2.5	FL3	FL4
Size:	240*120mm	○240*120mm ●320*160mm	○240*120mm ●320*160mm	○240*120mm ●320*160mm	○240*120mm ●320*160mm	○240*120mm ●320*160mm	○240*120mm ●320*160mm	○240*120mm ●320*160mm	○240*120mm ●320*160mm
Pixel Pitch:	0.9375mm	1.25mm	○1.579mm ●1.538mm	○1.579mm ●1.538mm	○1.875mm ●1.86mm	2mm	2.5mm	○3mm ●3.076mm	4mm
Weight(g):	○170g ●270g	○170g ●270g	○170g ●270g	○170g ●270g	○170g ●270g	○170g ●270g	○170g ●270g	○170g ●270g	○170g ●270g
SMD Chip:	Mini 4 in 1 COB available	SMD1010 COB available	SMD1212 COB available	SMD1212	SMD1515/ SMD1212	SMD1515	SMD1515	SMD2121	SMD2121
Smallest Curve Diameter	720mm in Diameter/90° Splicing								
Pixel density (dot/㎡)	1137777	640000	○401111 ●422500	○401111 ●422500	○284444 ●288906	250000	160000	○111111 ●105625	62500
Resolution:	256x128	○192*96 ●256*128	○152*76 ●208*104	○152*76 ●208*105	○126*64 ●172x86	○120*60 ●160*80	○96*48 ●128*64	○80*40 ●104x52	○60*30 ●80*40
Scan mode:	1/64	○1/48 ●1/64	○1/38 ●1/52	○1/38 ●1/53	○1/32 ●1/43	○1/30 ●1/40	○1/24 ●1/32	○1/20 ●1/26	○1/15 ●1/20
Refresh Rate	3840Hz	3840Hz	3840Hz	3840Hz	3840Hz	3840Hz	3840Hz	3840Hz	3840Hz
Brightness(cd/ ㎡)	500-600nit	600-700nit	700-900nit	700-900cd	700-900nit	700-900nit	700-900nit	700-900nit	700-900nit
Wattage (Max./Avg.)	600W/200W	600W/200W	600W/200W	600W/200W	600W/200W	600W/200W	600W/200W	600W/200W	600W/200W
Viewing Angle(H/V)	160°/140°								
CCT:	1000-10000K Changeable								
Contrast Ratio:	5000:1								
Maintenance:	Front								